



## **SS SC 4 AEROFLEX' PERFORATED SLIDING/FOLDING CLOSURE**

### **Curtain construction**

The top and bottom of each panel section is fitted with a 102mm high aluminium panel. This panel consists of an aluminium extrusion 2mm thick. It is connected into extruded hinge cleats with a 15° off-set to facilitate folding. The curtain is constructed of 152mm wide modules linked together by a continuous aluminium hinge. These hinges hold different curtain designs created by using different infills – in this case perforated aluminium holes approx 5mm diameter.

### **Overhead track**

Manufactured from a strong tempered aluminium alloy class 6351 –T6 Extrusion, 34mm wide x 42mm total height.

### **Locking**

Lock members are integral 50mm x 32mm standard extruded aluminium hollow posts. They are at both ends of each grille, at intervals of 2500mm maximum on full height doors and at 1500mm spacing (approx) on counter tops. Additional posts to support curves as necessary. Lead posts incorporate Adams Rite mortice locks operated by 5-pin cylinders on each side. Intermediate posts incorporate drop bolts locating into flush floor sockets. Drop bolts can be deadlocked with 5 pin cylinders.

### **Finishes**

Natural anodised or white, black, medium or light bronze powder coat paint

### **Weight**

Aeroflex – Approx 10kgs/m<sup>2</sup>

**Warranty**

All our products carry a minimum 1 year warranty from date of installation. The only exceptions are misuse, abuse or vandalism.